

Solum's technological breakthrough in the use of superior, lightweight barrier materials provides:

- Far superior protection against torch and tool attack when compared to any safe in common use today.
- Maximum protection and minimal loss of useable space with the use of excalibur's spaceage materials.
- Easy delivery to most high-rise buildings and situations with limited floor loads.

The World's to be to be the U.L. Approved to the U.

EXCALIBUR 60

The Cutting Edge of Security
Technology



The EXCALIBUR TRTL 60 × 6

FEATURING

SUPERIOR Protection against sophisticated

hurglary attack

SUPERIOR Peace of mind with the knowledge

that your valuables have been

secured to the maximum

SUPERIOR Insurance coverage

SUPERIOR Lightweight for easy installation

SUPERIOR Pricing for a 60 minute safe

The EXCALIBUR 60 replaces the TRTL30x6 safes as the standard for ultimate protection. Having been tested by Underwriters. Laboratories to withstand the rigorous torch and tool test on all six sides for twice as long as the TRTL30x6, the EXCALIBUR 60 has been granted the TRTL60x6 label, thereby being in a class by itself.



Many years of research and development have culminated in the creation of the EXCALIBUR 60 by Soltam, Ltd., a technological leader in Israel and throughout the world. Specializing in metallurgical products, including armaments, and using its knowledge of weapoury penetration. Soltam has created barriers of uniquely high resistance in order to thwart expert burglars who use their own sophisticated arsenal.

Precision engineering and proud craftsmanship ensure that each safe is manufactured to the strictest standards - our own



SPECIFICATIONS

DOOR AND BODY

The EXCALIBUR 60 door has an overall thickness of 8.2°; the five sides of the body each has a thickness of 4.8°. The core of this exceptional, yet streamlined, construction is composed of INFINITRIX, a technologically revolutionary material. Having the ability to successfully withstand concentrated torch and tool attacks over extensive periods of time, INFINITRIX is unparalleled in its capacity to prevent penetration. In addition, particularly sensitive areas of the EXCALIBUR 60 have been even further reinforced to deflect the most serious of attacks.

BOLTWORK

On engagement of the capstan handle, eight chromed steel bolts each of 1.6° diameter, are driven horizontally and vertically through reinforced individual bult chambers.

Additionally, the EXCALIBUR 60 door is secured firmly on the hinge side by the inclusion of 4 more

LOCKS AND RELOCKERS

The EXCALIBUR 60 includes a Surgent and Greenleaf U.L. Listed Group 1 Manipulation Proof combination lock plus a U.L. Listed key lock as standard equipment. The combination lock and key lock are each protected by a highly sensitized relocking system which is designed to activate in the event of a major attack.

FITTENGS AND FINISH

Adjustable and removable shelves are provided as standard. Compartments and special interiors are available as an option. The EXCALIBUR 60 features a durable and attractive textured finish, conveying the natural feeling of its strength while permitting the safe to blend subits into a business environment.


OPTIONS


- Dual combination locks
- Left swing door (right swing is standard)
- Mechanical and electronic timelock
- Special interiors


TRTL 60 × 6 DIMENSIONS & WEIGHTS











3400

5000


6000

6500

7000

MODE).	INTERIOR STORY					OFFICE DATES OF STREET				
	B	X	13	*	D	H		Ħ	Ą	þ
3400	3.5	*	14,3	×	193	* 483	×	29.3	×	32.7
	(864		500	2	495)	्राध्य	×	742	×	#31}
5000	49.3	×	19,7	B	19,5	38.8	×	29,3	X	32.7
	(1232		500	E	1951	(1494	×	742	Ħ	831)
6000	59		19.7	N	19.5	623	×	29.2	×	32.7
	(1499	*	500	*	493)	(1740)	¥	742	X	831)
6590	65	×	20	×	19.5	74.5	×	18.5	×	32.7
	(1651	x	737	H	495)	11892	×	4775	X	831)
2000	70	×	36	×	25	79.5	N	45.5	x	18.2
	(1778			777	1000	12020		1156	×	9715

DOUR SWING DIMENSIONS



DOOR SWING DIMENSIONS

MODIA.	A	R	C.13	D Sometica.	i ii	100	
3400	10.7	25.6	54,8	561.4	27.1	32.7	
3000	19.2	25.6	34K	60.4	27.1	127	
6VIIIO	19.7	25.6	348	623,4	27.3	132.7	
0.3400	29	ग्रह	73.4	60,7	36.4	32.7	
25,000	16.	41.9	87,4	57.7	43.4	38 ?	

All mensurements are minches.

LACKASAFE

Jaime Torrejon Director, Sales & Marketing

Office: 800-654-5213
Cell: 201-618-9424
Email: jaime@lackasafe.com
Web: www.lackasafe.com
Fax: 201-896-9204

Showroom

400 Meadow Lane Caristadt, NJ 07072



(See back of card)